

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**


PATENT NO. : 7,027,094 B2  
APPLICATION NO. : 09/885064  
DATED : April 11, 2006  
INVENTOR(S) : Amy E Battles et al.

Page 1 of 5

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

The title page showing the illustrative figure should be deleted to be replaced with the attached title page.

In the drawings:



On sheet 1 of 3, delete “

FIG. 1

” and

Signed and Sealed this

Seventh Day of September, 2010

*David J. Kappos*

David J. Kappos  
Director of the United States Patent and Trademark Office




FIG. 1

insert --

--, therefor.






FIG. 2


On sheet 2 of 3, delete “

” and



On sheet 3 of 3, delete “

FIG. 3 ” and



insert --

FIG. 3

--, therefor.

(12) **United States Patent**  
**Battles et al.**

(10) **Patent No.:** **US 7,027,094 B2**  
(45) **Date of Patent:** **Apr. 11, 2006**

(54) **MODELESS DIGITAL STILL CAMERA  
USING TOUCH-SENSITIVE SHUTTER  
BUTTON**

(75) **Inventors:** **Amy E Battles**, Windsor, CO (US);  
**Kenneth Jay Hall**, Windsor, CO (US);  
**David J Staudacher**, Ft Collins, CO  
(US)

(73) **Assignee:** **Hewlett-Packard Development  
Company, L.P.**, Houston, TX (US)

(\*) **Notice:** Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 817 days.

(21) **Appl. No.:** **09/885,064**

(22) **Filed:** **Jun. 21, 2001**

(65) **Prior Publication Data**

US 2002/0196357 A1 Dec. 26, 2002

(51) **Int. Cl.**  
**H04N 5/222** (2006.01)  
**H04N 5/225** (2006.01)  
**G03B 15/06** (2006.01)

(52) **U.S. Cl.** ..... **348/333.01; 396/374; 348/373**

(58) **Field of Classification Search** ..... **348/333.01,**  
**348/333.02, 333.05, 333.08, 333.09, 333.13,**  
**348/341, 372; 396/374**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,837,628 A 6/1989 Sasaki ..... 358/209  
4,885,643 A 12/1989 Ichimura et al. .... 358/335  
5,497,193 A 3/1996 Mitsuhashi et al. .... 348/231  
5,699,115 A \* 12/1997 Hiraki et al. .... 348/333.13  
5,845,161 A \* 12/1998 Schrock et al. .... 396/313

5,867,742 A 2/1999 Salvas et al. .... 396/263  
5,923,908 A \* 7/1999 Schrock et al. .... 396/263  
6,091,450 A \* 7/2000 Hirasawa ..... 348/333.01  
6,122,003 A \* 9/2000 Anderson ..... 348/207.99  
6,137,534 A 10/2000 Anderson ..... 348/222  
6,184,930 B1 2/2001 Mitsuhashi et al. .... 348/333.01  
6,535,694 B1 \* 3/2003 Engle et al. .... 396/263  
6,597,400 B1 \* 7/2003 Nishimura ..... 348/333.02  
6,734,910 B1 \* 5/2004 Yumoto et al. .... 348/333.05  
6,822,683 B1 \* 11/2004 Torikai ..... 348/333.13  
6,919,927 B1 \* 7/2005 Hyodo ..... 348/333.02  
2002/0054233 A1 \* 5/2002 Juen ..... 348/333.01  
2004/0183934 A1 \* 9/2004 Tatumiya ..... 348/333.02  
2005/0184972 A1 \* 8/2005 Tashiro et al. .... 348/173

**FOREIGN PATENT DOCUMENTS**

JP 54033030 A \* 3/1979  
JP 10313422 A \* 11/1998  
JP 1125488 A \* 9/1999  
JP 2000138854 A \* 5/2000  
JP 2000165705 A \* 6/2000  
JP 2003046856 A \* 2/2003

\* cited by examiner

*Primary Examiner*—Ngoc-Yen Vu

*Assistant Examiner*—John M. Villecco

(57) **ABSTRACT**

A modeless electronic imaging apparatus, such as a digital still camera, uses a touch-sensitive shutter button to automatically display "live" images from an image sensor whenever a user touches the shutter button. When the user is not touching the shutter button, the apparatus displays stored image data of the last stored image, or may display menu data according to actuation of system navigation buttons. The apparatus does not require the switching of modes between image capture mode and stored image display mode, but is always capable of image capture as well as stored image display.

**14 Claims, 3 Drawing Sheets**

